



Benner-Nawman, Inc.

3450 Sabin Brown Road • Wickenburg, AZ 85390
Phone: (800) 992-3833 or (928) 684-2813 Fax: (928) 684-7041
BNRebarTools.com

DIAMOND® Heavy-Duty Grade 60 Portable Rebar Benders



Model #HB-16W
#5 (5/8") Capacity
Bending Angle: 0-135 deg.
Bending Speed: 8 seconds
115V, 50/60Hz, 10 amps
Tool Weight: 33 lbs.



Model #DBR-25WH
#8 (1") Capacity
Bending Angle: 0-90 deg.
Bending Speed: 4 seconds
115V, 50/60Hz, 12 amps
Tool Weight: 57.3 lbs.



Model #DBD-16X
#5 (5/8") Capacity
Bending Angle: 0-180 deg.
Bending Speed: 5 seconds
115V, 50/60Hz, 10 amps
Tool Weight: 90 lbs.



Model #DBD-20X
#6 (3/4") Capacity
Bending Angle: 0-180 deg.
Bending Speed: 7 seconds
115V, 50/60Hz, 15 amps
Tool Weight: 134.5 lbs.



Model #DBD-25X
#7 (7/8") Capacity
Bending Angle: 0-180 deg.
Bending Speed: 6 seconds
115V, 50/60Hz, 12 amps
Tool Weight: 190 lbs.



Model #DBD-32X
#9 (1-1/8") Capacity
Bending Angle: 0-180 deg.
Bending Speed: 8 seconds
115V, 50/60Hz, 12 amps
Tool Weight: 397 lbs.

DBD-Series table-top rebar benders are shipped complete with a set of bending rollers and a foot pedal switch. Optional DBD-Series bender stands, combination cutter/bender units and workstations are available upon request.

Reliable and Portable -These rebar benders are compact for portability but very accurate, fast, dependable, and simple to operate. These units are easily transported from the shop to the job site.

Efficient and Powerful -115 Volt, 50/60 Hz electrically-driven mechanical systems, except for HB-16W & DBR-25WH benders are electrically-driven hydraulic systems. Available with 220V motors.

Two Pre-Set Angles -Bend any angle from 0 -180 degrees by using the angle selector, lock in one or two different angles for repeat bends. (Except for HB-16W & DBR-25WH)

Emergency Stop Button -Standard on the DBD-Series table-top rebar benders, pushing this red button stops the moving roller & returns it to the start position. (Not on HB-16W, DBR-25WH & DBD-32X)

Easy-Set Stopper -Keeps rebar straight between the moving and center rollers, quickly & easily adjustable to accommodate different sizes of rebar. (Except for HB-16W & DBR-25WH)

Bending Radius -A set of bending rollers is included to cover a wide range of rebar sizes. A bending chart makes it simple to select the correct combination of both moving and center rollers. The rebar bending radius is approximately 5D to 6D. (Except for HB-16W & DBR-25WH)

Foot Pedal Switch -A foot operated on/off switch is included with each DBD-Series table-top rebar bender for hands free operation. (Except for HB-16W & DBR-25WH)

In-place Applications -The HB-16W and DBR-25WH benders can be used to bend rebar protruding from a column or wall. HB-16W has an optional 90 deg. angle shoe & larger radius collar.

Straightening Applications -The push/pull hydraulic capability of the DBR-25WH bender can be used to easily straighten bent rebar. Larger radius bending shoes are available for DBR-25WH.

Warranty -One (1) year; includes parts and labor with Nationwide Authorized Warranty Centers.