



# Cordless Rebar Tying Tool Comparison between:

**Check out the Differences!**

**Both allow for one hand operation and reduce the risks of wrist & back injuries.**



**BN-TIER™**



**RE-BAR-TIER™**

Company Name Model Number	<b>Benner-Nawman, Inc.</b> <b>#BNT-64</b>	<b>MAX USA CORP.</b> <b>#RB515</b>
<b>Maximum Capacity Tying Rebar-Cylindrical Object-</b>	#10 (32 mm) x #10 (32 mm) with optional #64 Wire Guide 2.5" diameter (64mm) Max no Min	#8 (25mm) x #7 (22 mm) Max #5 (16mm) x #5 (16 mm) Min 1.85" diameter (47mm) Max
<b>Tool Weight</b>	6.7 lbs (3.0 kg) Without battery and wire spool	5.2 lbs (2.4 kg) Without battery and wire spool
<b>Tool Dimensions H x W X L (mm)</b>	7.02" x 3.12" x 25.74" (180 x 80 x 660) for horizontal work or covers to 11.31" x 3.12" x 22.62" (290 x 80 x 580) for vertical work	11.63" x 4" x 12" (340 x 100 x 340)  Requires an optional extension bar for horizontal work
<b>Number of Parts</b>	75	212
<b>Tying Speed</b>	1.6 seconds/tie	1.1 seconds/tie
<b>Wraps/Wire Per Tie</b>	Two wraps (18) gauge 1.0mm	3-4 wraps (21) gauge
<b>Wire Spool Length</b>	(148 ft) 45 m/coil	(312 ft.) 95 m/coil
<b>Wire Types</b>	Galvanized Wire*	Steel & Polyester Coated
<b>Ties Per Coil</b>	120 to 200 ties	75 to 90 ties
<b>Wire Spools Carton/Weight</b>	40 spools per carton 29 lbs. (13 kg) per carton	50 spools per carton 50 lbs. (22.7 kg) per carton
<b>Ties Per Charge</b>	750 ties/4-5 spools	375-450 ties/4-5 spools
<b>No. of Motors Motor Type</b>	Two (feeding and twisting) Tsukasa Brushless	Two (feeding and twisting) Brushless
<b>Torque Adjustment</b>	Yes	Yes
<b>Standard Equipment</b>	Plastic molded carrying case 2 Batteries and 1 Charger Ergonomic should strap #32 Wire Guide, 10 spools of wire	Plastic molded carrying case 2 Batteries and 1 charger Holster attaches to waist belt Instr. Video (English & Spanish)
<b>Battery Type</b>	Ni-Cd (nickel-cadmium)**	Ni-Cd (nickel-cadmium)
<b>Battery Voltage</b>	DC 12V	DC 9.6V (2.0 Ah)
<b>Recharging Time</b>	Approx. 30 minutes	Approx. 25 minutes
<b>Battery Charger</b>	110-240 VAC, 50/60Hz	115 VAC, 50/60Hz
<b>Average Retail</b>	\$1,459.00 each	\$2,559.00 each
<b>Wire Spool Retail</b>	\$3.50 each spool (galvanized)	\$4.25 each spool (steel)
<b>Warranty Period</b>	One Year Limited	One Year Limited

\* BNT-64 will have a polyester coated wire by Fall of 2009

\*\* BNT-64 will have Ni-Mh batteries (1,000 ties per charge) and a 115 Volt power to 12 Volt converter by Fall 2009