

Rebar Tying Tool Comparison between: BN-TIER #BNT-64 and **MAX**#RB650A



**Check out
BN-TIER's
advantages**



BNrebartools.com



Company Name Model Number	Benner-Nawman, Inc. <i>BN-TIER #BNT-64</i>	Max USA Corp. <i>#RB650A</i>
Max. Tying Capacity with #64 wire guide	#10 (32 mm) x #10 (32 mm)	#9 (29 mm) x #8 (25 mm)
Tool Weight	8.4 lbs (3.8 kg) With battery and wire spool	8.2 lbs (3.7 kg) With battery and wire spool
Tool Dimensions H x W X L (mm)	7.02" x 3.12" x 25.74" (180 x 80 x 660) for horizontal work or converts to 11.31" x 3.12" x 22.62" (290 x 80 x 580) for vertical work	13.13" x 4" x 14.5" (334 x 102 x 368) Requires optional extension bar for horizontal work.
Number of Parts	75	211
Tying Speed	1.6 seconds/tie	1.1 seconds/tie
Wraps/Wire Per Tie	Two wraps (18) gauge 1.0mm	One wrap (16) gauge 1.5mm
Wire Spool Length	(148 ft) 45 m/coil	(82 ft.) 25 m/coil
Wire Types	Galvanized Wire only	Steel, Galv. & Polyester Coated
Ties Per Coil	120 to 200	110 to 210 ties
Wire Spools Carton/Weight	40 spools per carton 29 lbs. (13 kg) per carton	50 spools per carton 50 lbs. (22.7 kg) per carton
Ties Per Charge	750 ties/charge 4-5 spools	300 ties/charge 2-3 spools
Torque Adjustment	Yes	Yes
Standard Equipment with #32 wire guide up to #6 x #6 rebars	Plastic molded carrying case 2 Batteries and a charger Ergonomic should strap 10 spools of galv. wire	Plastic molded carrying case 2 Batteries and a charger Holster attaches to waist belt Instr. Video (English & Spanish)
Battery Type	Ni-Cd (nickel-cadmium)	Ni-Mh (nickel metal hydride)
Battery Voltage	DC 12V	DC 9.6V
Recharging Time	Approx. 30 minutes	Approx. 30 minutes
Battery Charger	110-240 VAC, 50/60Hz	115 VAC, 50-60 Hz
Mfg. Suggested List	\$1,800.00	\$3,030.78
Wire Spool List Price	\$3.00 each (galvanized)	\$5.48 each (steel)
Warranty Period	One Year Limited	One Year Limited