



GS710 GAS CUT-OFF SAW

From our streamlined design to our reliable performance and our incredible cost advantage, it is easy to see the benefits of going with a ZENT® Saw.



Engine	Air cooled two cycle engine
Displacement	71cc
Engine Power	4.4 hp (3.2kW)
Weight (Without Blade)	22.8 lbs (10.4kg)
Fuel Capacity	24 oz. (0.7L)
Blade Diameter	14" (350mm)
Cutting Depth	5" (125mm)
Arbor size	1" (25.4mm)
Blade Shaft Speed	5,400 rpm

- Two piston rings are better than one. The Zent saw has two piston rings which make it more efficient and extends the life of the engine. Competitors like the Makita® only have one ring.
- The Zent has ceramic coated cylinders much like the ones you would find in a racecar. The coating reduces friction and wind resistance so more air is drawn into the combustion chamber, which results in better fuel mixture, more power, and longer engine life.
- The Zent carburetor is the same model used in Husqvarna® and Stihl® saws.
- Zent's patented air duct system has angled fan blades on the flywheel that dramatically increases the air flow over the cylinder increasing power and efficiency.
- The Zent saw has a two stage (foam and fiber) air filter. A new three stage air filter will be introduced in October 2008 for existing and new models.

- A sealed clutch lubrication system prevents oil from leaking on the shaft. Most other saws use an open oil lubrication system which can leak and cause maintenance problems. With the sealed clutch Zent saws don't have that problem.
- A cylinder pressure release valve releases the pressure from in the cylinder and makes pulling the start cord much easier than the competition.
- The Zent has a powerful 71cc 4.4 hp engine that is strong enough for your highest quality blades.
- A speed regulator prevents over revving, keeping your saw from breaking down and extending the life of your blades.
- Prepaid Freight on orders of two tools or more.
- Full 90 Day Warranty



Benner-Nawman, Inc.

3450 Sabin Brown Road • Wickenburg, Arizona 85390
 (800) 992-3833 • (928) 684-2813 • Fax (928) 684-7041
 mail@bnproducts.com